


INTRODUCING QUANTUM (LEVEL II AND IIIA)



WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

QUANTUM™
BALLISTIC VEST

MODEL: _____
 LAST NAME: _____
 FIRST NAME: _____
 SIZE: _____
 SERIAL #: _____
 LOCATION OF MANUFACTURE: CENTRAL LAKE, MI 49822
 DATE OF MANUFACTURE: _____
 DATE OF ISSUE: _____
 MANUFACTURER'S DECLARED WARRANTY PERIOD: 5 YEARS
 SALES ORDER NUMBER: _____
 THREAT LEVEL: NIJ-0101.06

This model of armor has been determined to comply with NIJ Standard-0101.06 by the NIJ Compliance Testing Program and is listed on the NIJ Compliant Protective List.

WARNING!
This garment is rated ONLY for the ballistic threat level stated above. It is NOT intended to protect against rifle fire or sharp-edged or pointed instruments.

BALLISTIC PAD CARE INSTRUCTIONS
 1. Wipe with damp cloth.
 2. DO NOT MACHINE WASH or MACHINE DRY.
 3. DO NOT BLEACH, DRY CLEAN or IRON.

ARMOR EXPRESS™
PROTECTION

788 N. W. 88 - PO BOX 516 - CENTRAL LAKE, MI 49822

WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

INNOVATIVE FEATURES

- Robust & durable design
 - Proven strength for peace of mind
- Detailed specifications available upon request*

COMMON SPECIAL THREATS

**Armor tested to varying rounds - see preceding pages for exact threats tested*

II

IIIA



5.7 x 28, 40 gr. FNH
SS197SR

5.7 x 28, 40 gr. FNH
SS197SR



9mm, 124 gr. Luger +P
GDHP

9mm, 124 gr. Luger +P
GDHP



.357 SIG, 125 gr. Gold
Dot HP

12 Gauge, 1 oz. Rifled
Slug



.44 Rem. Magnum,
240 gr. Hydra-Shok

Certified to NIJ-0101.06 ballistic requirements



Outstanding performance - Armor Express' workhorse in the Law Enforcement community, the Quantum brings '06 stopping power ballistics at an affordable cost.

Amazing protection - Providing next-generation protection, with special threat capabilities, the Quantum ballistic package is a robust solution. Capable of stopping the 5.7x28 Sporting Round (both II and IIIA), and passing the DEA Protocol (IIIA) peace of mind is granted.

QUANTUM

LEVEL II

TECHNICAL SPECIFICATIONS

Model Designation	QTM-B-II
Certified to NIJ-0101.06 Threat Level	II
Test ID #	AEX09-001649
NIJ Certified Sizes	C1 - C5
Gender	Neutral
Ballistic Material	100% Twaron® Fiber
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	1.02 lbs/ft ²
Thickness	0.240 in
V-50 - 9mm	1,662 ft/s
V-50 - .357 Mag.	1,610 ft/s
Certification BFS - 9mm	28.8 mm
Certification BFS - .357 Mag.	34.30 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
S&W .44 REM. MAG	240gr. HYDRA-SHOK P44HSI
S&W M&P .357 SIG	SPEER LE 125gr. GDHP 54234
S&W M&P 9mm	SPEER LE 124gr. GDHP 53617
FN HERSTAL 5.7x28	40gr. SS197SR V-MAX

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

QUANTUM^{GEN2}

LEVEL IIIA

TECHNICAL SPECIFICATIONS

Model Designation	QTMG2-A-III A
Certified to NIJ-0101.06 Threat Level	III A
Test ID #	AEX09-002396
NIJ Certified Sizes	C1 - C5
Gender	Neutral
Ballistic Material	Twaron® Flex Woven Aramid & Twaron Laminate
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	1.26 lbs/ft ²
Thickness	0.250 in
V-50 - .357 SIG	1,827 ft/s
V-50 - .44 Mag.	1,719 ft/s
Certification BFS - .357 SIG	27.9 mm
Certification BFS - .44 Mag.	36.1 mm
Warranty	5 Years

Passed DEA protocol dated 12-03-2009

SPECIAL THREATS*

Weapon	Ammunition
S&W M&P 9mm	SPEER LE 124 Gr. GDHP 53617
FN HERSTAL 5.7x28	SS197SR 40gr V-Max
FN HERSTAL 5.7x28	SS195LF 27gr

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

QUANTUM *FEMALE*

LEVEL II

TECHNICAL SPECIFICATIONS

Model Designation	QTMF-B-II
Certified to NIJ-0101.06 Threat Level	II
Test ID #	AEX09-001644
NIJ Certified Sizes	C1 - C5
Gender	Female
Ballistic Material	100% Twaron® Fiber
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	1.05 lbs/ft ²
Thickness	0.240 in
V-50 - 9mm	1,646 ft/s
V-50 - .357 Mag.	1,621 ft/s
Certification BFS - 9mm	30.80 mm
Certification BFS - .357 Mag.	35.70 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
S&W .44 REM. MAG.	240gr. HYDRA-SHOK P44HSI
.45 WIN MAG GRIZZLY MARK 1	.45 WIN MAG 230gr. RN/TCJ
S&W M&P .357 SIG	SPEER LE 125gr. GDHP 54234
S&W M&P 9MM	SPEER LE 124gr. GDHP 53617
FN HERSTAL 5.7x28	40gr. SS197SR V-MAX

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

QUANTUM *FEMALE*

LEVEL IIIA

TECHNICAL SPECIFICATIONS

Model Designation	QTMF-C-III A
Certified to NIJ-0101.06 Threat Level	IIIA
Test ID #	AEX09-001727
NIJ Certified Sizes	C1 - C5
Gender	Female
Ballistic Material	100% Twaron® Fiber
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	1.32 lbs/ft ²
Thickness	0.310 in
V-50 - .357 SIG	1,775 ft/s
V-50 - .44 Mag.	1,625 ft/s
Certification BFS - .357 SIG	27.4 mm
Certification BFS - .44 Mag.	37.3 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
S&W M&P 9MM	SPEER LE 124gr. GDHP 53617
BROWNING 12ga.	LEB127LRS 1oz. Rifled slug FED 2 3/4" TAC.
FN HERSTAL 5.7x28	27gr. SS195LF
FN HERSTAL 5.7x28	40gr. SS197SR V-MAX

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.