


INTRODUCING SERAPH *GEN2* (LEVEL II AND IIIA)



WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

SERAPH

MODEL: _____

LAST NAME: _____

FIRST NAME: _____

SIZE: _____

LOT # _____ SERIAL # _____ 788 N. W. 88

LOCATION OF MANUFACTURE: CENTRAL LAKE, MI 49822

DATE OF MANUFACTURE: _____

DATE OF ISSUE: _____

MANUFACTURER'S DECLARED WARRANTY PERIOD: 5 YEARS

SALES ORDER NUMBER: _____

THREAT LEVEL: NIJ 0101.06

This model of armor has been determined to comply with NIJ Standard 0101.06 by the NIJ Compliance Testing Program and is listed on the NIJ Compliant Products List.

WARNING!
This garment is rated ONLY for the ballistic threat level stated above. It is NOT intended to protect against rifle fire or sharp-edged or pointed instruments.

BALLISTIC PAD CARE INSTRUCTIONS

1. Wipe with damp cloth.
2. DO NOT MACHINE WASH or MACHINE DRY.
3. DO NOT BLEACH, DRY CLEAN or IRON.

ARMOR EXPRESS

788 N. W. 88 - PO BOX 516 - CENTRAL LAKE, MI 49822

WEAR FACE - THIS SIDE TO BE WORN AGAINST BODY

INNOVATIVE FEATURES

- Low profile construction
- Light build for extended comfort
- Additional stopping power

Detailed specifications available upon request

COMMON SPECIAL THREATS

**Armor tested to varying rounds - see proceeding pages for exact threats tested*


II

IIIA



5.7 x 28, 40 gr. FNH
SS197SR

5.7 x 28, 40 gr. FNH
SS197SR



9mm, 124 gr. Luger +P
GDHP

5.7 x 28, 27 gr. FNH
SS195LF



.357 SIG, 125 gr. Gold
Dot HP

9mm, 124 gr. Luger +P
GDHP



.44 Rem. Magnum,
240 gr. Hydra-Shok

12 Gauge, 1 oz. Rifled
Slug

Certified to NIJ-0101.06 ballistic requirements



Outstanding performance - For officers who want it all: thinness, low weight, and excellent flexibility. Seraph™ ballistics are second to none.

Top tier protection - The second generation of Seraph™ armor has been built to match the most strenuous requirements, including our in-house special threat ballistic testing. Both level II and IIIA Seraph Gen2 models are capable of stopping some of the most advanced rounds, including the 5.7 x 28 Sporting Round (both II and IIIA) and the 5.7 x 28 Lead Free (IIIA).

SERAPH^{GEN2}

LEVEL II

TECHNICAL SPECIFICATIONS

Model Designation	SERG2-A-II
Certified to NIJ-0101.06 Threat Level	II
Test ID #	AEX09-002034
NIJ Certified Sizes	C1 - C5
Gender	Neutral
Ballistic Material	Twaron® Microfilament Flex Woven Aramid & Dyneema® SB70
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	0.79 lbs/ft ²
Thickness	0.203 in
V-50 - 9mm	1,744 ft/s
V-50 - .357 Mag.	1,624 ft/s
Certification BFS - 9mm	32.6 mm
Certification BFS - .357 Mag.	35.57 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
S&W M&P 9mm	127gr. +P+ Ranger T-Series
FN HERSTAL 5.7x28	40gr. V-Max FNH SS197SR
S&W M&P .357 SIG	125gr. GDHP
S&W .44 MAG	240gr. Federal Hydra-Shok

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

SERAPH^{GEN2}

LEVEL IIIA

TECHNICAL SPECIFICATIONS

Model Designation	SERG2-A-III A
Certified to NIJ-0101.06 Threat Level	III A
Test ID #	AEX09-002035
NIJ Certified Sizes	C1 - C5
Gender	Neutral
Ballistic Material	Twaron® Microfilament Flex Woven Aramid & Dyneema® SB70
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	1.12 lbs/ft ²
Thickness	0.275 in
V-50 - .357 SIG	1,828 ft/s
V-50 - .44 Mag.	1,672 ft/s
Certification BFS - .357 SIG	31.4 mm
Certification BFS - .44 Mag.	39.5 mm
Warranty	5 Years

Passed DEA protocol

SPECIAL THREATS*

Weapon	Ammunition
S&W M&P 9mm	124gr. Luger +P GDHP
FN HERSTAL 5.7x28	40gr. FNH SS197SR
FN HERSTAL 5.7x28	27gr. FNH SS195LF
BROWNING 12ga.	LE127RS 1oz. Rifled slug FED 2 3/4" TAC.

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

SERAPH *GEN2 FEMALE*

LEVEL II

TECHNICAL SPECIFICATIONS

Model Designation	SERFG2-B-II
Certified to NIJ-0101.06 Threat Level	II
Test ID #	AEX09-002352
NIJ Certified Sizes	C1 - C5
Gender	Female
Ballistic Material	Twaron® Microfilament Flex Woven Aramid & Dyneema® UHMWPE
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	0.85 lbs/ft²
Thickness	0.210 in
V-50 - 9mm	1,825 ft/s
V-50 - .357 Mag.	1,721 ft/s
Certification BFS - 9mm	31.70 mm
Certification BFS - .357 Mag.	35.60 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
S&W M&P 9mm	Speer LE 124gr. GDHP 53617
Mark 1 .45 WIN MAG	230RNTCJ
S&W .40	165 GDHP
FN HERSTAL 5.7x28	SS197SR V-MAX
S&W M&P .357 SIG	125gr. GDHP 54324
.44 REM. MAG	240gr. HYDRA-SHOK JHP

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

SERAPH GEN2 FEMALE

LEVEL IIIA

TECHNICAL SPECIFICATIONS

Model Designation	SERFG2-A-III A
Certified to NIJ-0101.06 Threat Level	III A
Test ID #	AEX09-002306
NIJ Certified Sizes	C1 - C5
Gender	Female
Ballistic Material	Twaron® Microfilament Flex Woven Aramid & Dyneema® UHMWPE
Pad Cover	Seam-sealed, waterproof Ripstop Nylon

Weight (Areal Density)	1.18 lbs/ft ²
Thickness	0.300 in
V-50 - .357 SIG	1,881 ft/s
V-50 - .44 Mag.	1,753 ft/s
Certification BFS - .357 SIG	30.6 mm
Certification BFS - .44 Mag.	37.6 mm
Warranty	5 Years

SPECIAL THREATS*

Weapon	Ammunition
FN HERSTAL 5.7x28	SS195LF 27 gr.
FN HERSTAL 5.7x28	SS197SR V-MAX 40 gr.
BROWNING 12ga.	LE127RS 1oz. Rifled slug FED 2 3/4" TAC.
S&W M&P 9MM	SPEER LE 124gr. GDHP 53617

*Special threat testing conducted in the Armor Express' state-of-the-art Ballistic Research Laboratory using the NIJ-0101.06 shot pattern.

